

Ground Fault Products

Hard Wired 30 Ampere GFCI - NEMA Type 4X



Applications

Power Generators
Submersible Pumps
Textile

Agricultural Equipment
Cement Cutting Equipment
Food Processing

Production Assembly Equipment
Spa and Hot Tubs
Vending Equipment



Circuit Guard® Hard Wired 30A GFCI - UL Type 4X Rated

Description	Voltage	Alarm	Manual Set	Automatic Set
Hard wired, manual set and automatic set GFCIs.	120V AC	None	GFHW13005	GFHW13105
	120V AC	Audible	GFHW13015	GFHW13115
	240V AC	None	GFHW23005	GFHW23105
	240V AC	Audible	GFHW23015	GFHW23115
	120/240V AC	Audible	GFHW33015	GFHW33115
	3Ø 250V AC	None	GFHW530	GFHW531
	3Ø 120/208V AC	None	GFHW430	GFHW431

Note: All units above are stock items.

Specifications

Electrical Ratings	
Rated Voltage	120V AC, 240V AC and 120/240V, 3Ø 250V AC, 3Ø 120/208V AC.
Operating Voltage Range	85% to 110%.
Current	Up to 30A or device rating.
Frequency	60 Hz.
Trip Level	4-6 mA.
Phase	Single.
Response Time	.025 sec. Max.
Dielectric Withstand	1500 VRMS across contact, 4000 VRMS between conductors and enclosure.
Surge Withstand	6000V impulse, 0.5 microseconds rise time 100kHz ringing frequency with 40% decay per cycle.
Let Go Line Voltage	60% of rated.
Grounded Neutral Detection	6 Ohms or less.
Power Up	Manual or automatic reset.
Environmental Ratings	
Housing Rating	UL Type 4X.
Construction	Industrial grade design.
Type	Class A GFCI.
Operating Temperature	-35°C to 66°C, -30°F to 150°F.
Leakage Current @ 93% Humidity	Zero.
Features	
Life (Endurance)	10,000 cycles (6000 with load and 4000 without load).
Grounded Neutral Protection	Open neutral protection Trips upon loss of neutral.
Power On Indicator	Trips if ground and neutral touch at load side.
Power Off Indicator	Green light on.
Wiring Application	Red blinking light plus optional audible alarm.
Switch Interface	3 Wire Single Phase (Hot, Neutral and Ground),
Latching Mechanism	4 Wire Single Phase (Line 1, Line 2, Neutral and Ground).
Physical Specifications	Double Insulated.
Wire Leads	#10 AWG, 24" long.
Unit Color	Gray with black cover.
Label Color on Portable and Hard Wired Units	Automatic reset: yellow background with black lettering.
Weight	Manual reset: black background with yellow lettering.
	1.40 lbs.


Related Code

Confined Space	OSHA 29 CFR 1926.404 (b) (1) (ii) OSHA 29 CFR 1926.405 (a) (2) (ii) (G)
Construction Sites	NEC 590.6
Commercial Garages	NEC 511.12
Fountains	NEC 680.5B
Spas and Hot Tubs	NEC 680.40
Marinas	NEC 555.3


Automatic Reset GFCI



Manual Reset GFCI



Dimensional Drawing



Side View

Dimensions in Inches (mm)