



Watertight Devices

15 and 20 Ampere, Straight Blade Devices

IP65, 66, 67
SUITABILITY



14W33H

15A Straight Blade Plugs

Description	Color	Cord Dia.	Catalog Number		
Thermoplastic elastomer plugs.	Yellow	.300"-.625" (7.6-15.9)	14W47H	14W49H	14W07H[▲]
	Black		14W47HBK	—	—



2P 3W
15A 125V
NEMA 5-15P
UL CSA



2P 3W
15A 250V
NEMA 6-15P
UL CSA



3P 3W
15A 125V
10A 600V
NON-NEMA



15W47H

15A Straight Blade Connectors/Receptacles*

Description	Color	Cord Dia.	Catalog Number		
Thermoplastic elastomer connectors.	Yellow	.300"-.625" (7.6-15.9)	15W47H	15W49H	15W07H[▲]
	Black		15W47HBK	—	—
Thermoplastic elastomer receptacles.	Yellow	—	60W47H	60W49H	—



2P 3W
15A 125V
NEMA 5-15R
UL CSA
0.5 HP



2P 3W
15A 250V
NEMA 6-15R
UL CSA
1.5 HP



3P 3W
15A 125V
10A 600V
NON-NEMA



60W47H

IP65, 66, 67
SUITABILITY

20A Straight Blade Plugs*

Description	Cord Dia.	Catalog Number		
Thermoplastic elastomer yellow plugs.	.300"-.625" (7.6-15.9)	14W33H	14W48H	—



2P 3W
20A 125V
NEMA 5-20P
UL CSA



2P 3W
20A 250V
NEMA 6-20P
UL CSA

20A Straight Blade Connectors/Receptacles*

Description	Cord Dia.	Catalog Number		
Thermoplastic elastomer yellow connectors.	.300"-.625" (7.6-15.9)	15W33H*	15W48H*	—
Thermoplastic elastomer yellow receptacles.	—	60W33H	60W48H	—



2P 3W
20A 125V
NEMA 5-20R
UL CSA
1 HP



2P 3W
20A 250V
NEMA 6-20R
UL CSA
2 HP

Note: * Receptacles are NEMA 3R, IP44 suitability.
Horsepower ratings for receptacle/plug connection are AC voltage only.
▲ CSA certified only.
• UL listed only.