

Rigid/intermediate grade conduit fittings

Conduit clamps, straps, hangers

CLAMPS – MALLEABLE IRON

Applications:

- To support rigid conduit and IMC to mounting surface

Options:

- Description** **Suffix**
- Hot dip galvanized **HDG**

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
510	1/2"	100	6
511	3/4"	50	8
512	1"	50	13
513	1 1/4"	25	20
514	1 1/2"	20	30
515	2"	10	64
516 [ⓐ]	2 1/2"	5	104
517 [ⓐ]	3"	2	120
518 [ⓐ]	3 1/2"	2	150
519 [ⓐ]	4"	2	220
520 [ⓐ]	5"	1	380
521 [ⓐ]	6"	1	690

[ⓐ]Also for use with thin wall (EMT) conduit.
[ⓐ]Not UL Listed.

CLAMPBACKS/SPACERS – MALLEABLE IRON

Applications:

- To provide space between conduit and mounting surface

Standard materials:

- Stamped steel – 1/2" - 1 1/2"
- Malleable iron – 2" - 6"

Options:

- Description** **Suffix**
- Hot dip galvanized **HDG**

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1 [ⓐ]	1/2"	25	8
CB2 [ⓐ]	3/4"	25	10
CB3 [ⓐ]	1"	25	12
CB4 [ⓐ]	1 1/4"	25	21
CB5 [ⓐ]	1 1/2"	25	42
CB6	2"	10	40
CB7	2 1/2"	10	49
CB8	3"	10	62
CB9	3 1/2"	10	91
CB10	4"	10	110
CB11 [ⓐ]	5"	5	135
CB12 [ⓐ]	6"	5	225

[ⓐ]Stamped steel.
[ⓐ]Not UL Listed.

STRAPS – STEEL GALVANIZED

Applications:

- Used to secure rigid conduit or IMC to mounting surface

Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
496 2	3/8"	250	2
496 3	1/2"	150	2
496 4	3/4"	100	3
496 5	1"	50	7
496 6	1 1/4"	50	8
496 7	1 1/2"	50	10
496 8	2"	25	15
496 9	2 1/2"	25	19
496 10	3"	25	23
496 11	3 1/2"	25	93
496 12	4"	10	108

CLAMPS – STEEL

Applications:

- To support rigid conduit and IMC to mounting surface

Heavy gauge



Cat. #	Size	Unit qty.	Wt. lbs. per 100
410	1/2"	100	5
411	3/4"	50	6
412	1"	50	11
413	1 1/4"	50	13
414	1 1/2"	25	20
415	2"	25	22
206	2 1/2"	25	64
207	3"	25	71
208	3 1/2"	10	120
209	4"	10	130

CLAMPS "SNAP-ON – STEEL

Applications:

- To support rigid conduit and IMC to mounting surface

Light gauge



Cat. #	Size	Size of strap inside	Unit qty.	Wt. lbs. per 100
567	3/8"	.675	200	2

Rigid/intermediate grade conduit fittings

Conduit clamps, straps, hangers

Rigid fittings

CABLE AND CONDUIT HANGERS – STEEL

Certifications and compliances:

- UL Listed

With Bolt



Cat. #	Conduit sizes		Unit qty.	Wt. lbs. per 100
	EMT	Rigid		
0B	1/2"	3/8" and 1/2"	100	6
1B	3/4"	3/4"	100	6
2B	1"	1"	100	8
2 1/2 B	1 1/4"	-	100	10
3 B	1 1/2"	1 1/4"	100	11
4 B	-	1 1/2"	100	16
5 B	2"	2"	50	23
6 B	2 1/2"	2 1/2"	50	29
7 B	3"	3"	25	31
8 B	3 1/2"	3 1/2"	10	38
9 B	4"	4"	10	38

CABLE AND CONDUIT HANGERS – STEEL

Applications:

- Used to provide mechanical support to conduit and raceway systems

Certifications and compliances:

- UL Listed
- cUL Listed

With extruded hole and bolt



Cat. #	Description	Unit qty.	Wt. lbs. per 100
0BX	3/8 and 1/2 RGD 1/2 EMT	100	6
1BX	3/4 RGD 3/4 EMT	100	7
2BX	1 RGD 1 EMT	100	11
2 1/2BX	1 1/4 EMT	100	10
3BX	1 1/4 RGD 1 1/2 EMT	100	13
4BX	1 1/2 RGD	100	16
5BX	2 RGD 2 EMT	50	17

BEAM CLAMPS/INSULATOR SUPPORTS – MALLEABLE IRON

Standard finish:

- Zinc plated


UL File No. E-184283



Cat. #	Base size	Jaw opening	Max. wt. support	Tapped holes	Unit qty.	Wt. lbs. per 100
528	3/4"	5/8"	50	10 - 24	25	14
529	3/4"	5/8"	50	1/2" - 20	25	13
530	1"	3/4"	60	10 - 24	25	23
531	1"	3/4"	100	1/4" - 20	25	24
532	1 1/2"	7/4"	80	3/8" - 18	50	47
533	2"	7/8"	100	3/8" - 16	25	81
534	2 1/2"	7/8"	200	1/2" - 13	25	155

Dimensions (in inches):

Cat. #	A	B	C	Max. beam thickness
528	1.10	1.23	0.56	1/2"
529	1.10	1.25	0.57	1/2"
530	1.37	1.37	0.67	5/8"
531	1.25	1.39	0.69	5/8"
532	1.47	1.57	0.91	7/8"
533	1.75	1.82	1.12	1"
534	2.28	2.15	1.04	1"



BEAM CLAMPS/INSULATOR SUPPORTS – STEEL



Cat. #	Base Size	Jaw Opening	Tapped Holes	Unit qty.	Wt. lbs. per 100
529 S	3/4"	5/8"	1/4" - 20	50	13